



### Main

Range	Acti 9
Range of product	IC60 IID ISW-NA IDPN Vigi
Product or component type	Undervoltage release
Device short name	IMN
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

### Complementary

Range compatibility	Acti 9: Acti 9 iDPN (China version) Acti 9: Acti 9 iDPN Vigi Acti 9: Acti 9 iC40 Acti 9: Acti 9 iC65 Acti 9: Acti 9 ARA Acti 9: Acti 9 iID Acti 9: Acti 9 iSW-NA Acti 9: Acti 9 RCA Acti 9: Acti 9 iC60 (double terminals miniature circuit breaker)
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm

Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 8 mm <sup>2</sup> rigid Clamp terminal 2 cable(s) 2.7 mm <sup>2</sup> rigid Clamp terminal 1 cable(s) 6 mm <sup>2</sup> flexible Clamp terminal 2 cable(s) 2.7 mm <sup>2</sup> flexible with cable end cable end
Tightening torque	1 N.m
Market segment	Residential Small commercial

## Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------