



Main

Range	Acti 9 Clario Librio Prodis
Range of product	Clario ID Librio ProDis
Product or component type	OC contact
Device short name	OFS
Signal contacts composition	1 C/O
[In] rated current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC
9 mm pitches	1

Complementary

Range compatibility	Acti 9 RCCB-ID Acti 9 ID C40 Acti 9 IDc Acti 9 ITG40
Mounting mode	Fixed
Mounting support	DIN rail
Height	85.3 mm
Width	9 mm
Depth	78.5 mm
Product weight	33 g
Colour	White
Connections - terminals	Clamp terminal in bottom 2 cable(s) 1.5 mm ² flexible Clamp terminal in bottom 1 cable(s) 0.5...2.5 mm ² rigid Clamp terminal in bottom 2 cable(s) 1.5 mm ² flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

Product compatibility	ITG40 IDc ID C40
Market segment	Residential Small commercial

Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	0.95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0716 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------