

GENERAL

Measuring and protection transformers. Wound primary, bus-bar, split core and narrow profile transformers
For cable or bus-bar.
Plastic or resin encapsulated casing (depending on type).
With fixing support and/or bar enclosing screws depending on type.
Fixing to DIN rail (on request)

STANDARDS

IEC 185
UNE EN 61869 (IEC 61869)
VDE 0414
IEC 801/1-3.4
DIN 57414
BS 3938
EN 50081
EN 50082
IEC 1010

GENERAL TECHNICAL SPECIFICATIONS

Security factor	$F_s < 5$
Rated voltage (maximum)	720 V
Test voltage	3 kV A.C. (1 min)
Frequency	50-60 Hz
Rated short-time thermal current	$I_{th} = 60 I_n$ for wound primary transformers. I_{th} limited by cable sizes or primary bus-bar for other cases.
Rated dynamic current	$I_{Dyn} = 2,5 \times I_{th}$
Continuous overload	$I_D = 1,2 \times I_N$
Operating temperature	-10...50 °C.
Accuracy	0,5 ; 1 and 3 (0,2S, 0,5S on request)
Rated secondary current	/5 or /1 A
Insulation class	Class E Class B (130 °C) Available

MEASURING TRANSFORMERS (PLASTIC CASING)



BUS-BAR TRANSFORMERS									
MODEL	TL2			TL3			TL4		
Bus-Bar	100x20			100x30			100x60		
Cable	Ø20			Ø30			Ø60		
Accuracy Class	0,5	1	3	0,5	1	3	0,5	1	3
I _{pn} (A)	VA			VA			VA		
750	10	20	30						
800	15	20	30						
1000	20	30	45						
1200	20	30	45						
1500	30	45	60	10	20	30			
2000	30	60	90	15	25	40	10	20	30
2500				25	30	45	10	20	30
3000				30	45	60	20	30	45
4000							30	60	90
5000							30	60	90

DIMENSIONS

MODELS	A	B	C	D	E	F
TL2	102	20	94	178	38	66
TL3	103	32	114	210	45	71
TL4	104	62	156	224	50	78

Dimensions in mm.