



### Main

|                                 |                       |
|---------------------------------|-----------------------|
| Range of product                | Harmony XB4           |
| Product or component type       | Complete pilot light  |
| Device short name               | XB4                   |
| Bezel material                  | Chromium plated metal |
| Fixing collar material          | Zamak                 |
| Mounting diameter               | 22 mm                 |
| Sale per indivisible quantity   | 1                     |
| Shape of signaling unit head    | Round                 |
| Cap/Operator or lens colour     | White                 |
| Operator additional information | With plain lens       |
| Light source                    | Protected LED         |
| Bulb base                       | Integral LED          |
| Light source colour             | White                 |
| [Us] rated supply voltage       | 24 V AC/DC, 50/60 Hz  |

### Complementary

|  |  |
|--|--|
| Height                                 | 47 mm  |
| Width                                  | 30 mm  |
| Depth                                  | 54 mm  |
| Terminals description ISO n°1          | (X1-X2)PL  |
| Product weight                         | 0.08 kg  |
| Resistance to high pressure washer     | 7000000 Pa at 55 °C, distance: 0.1 m   |
| Connections - terminals                | Screw clamp terminals : $\leq 2 \times 1.5 \text{ mm}^2$ with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals : $1 \times 0.22...2 \times 2.5 \text{ mm}^2$ without cable end conforming to EN/IEC 60947-1 |
| [Ui] rated insulation voltage          | 250 V (degree of pollution: 3) conforming to EN 60947-1  |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to EN 60947-1  |
| Signalling type                        | Steady   |
| Supply voltage limits                  | 19.2...30 V DC   |

21.6...26.4 V AC

|                     |                                     |
|---------------------|-------------------------------------|
| Current consumption | 18 mA                               |
| Service life        | 100000 h at rated voltage and 25 °C |
| Surge withstand     | 1 kV conforming to IEC 61000-4-5    |


## Environment

|  |  |
|--|--|
| Protective treatment                       | TH   |
| Ambient air temperature for storage        | -40...70 °C  |
| Ambient air temperature for operation      | -40...70 °C  |
| Class of protection against electric shock | Class I conforming to IEC 60536  |
| IP degree of protection                    | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K  |
| NEMA degree of protection                  | NEMA 13<br>NEMA 4X   |
| IK degree of protection                    | IK06 conforming to IEC 50102   |
| Standards                                  | EN/IEC 60947-5-4<br>CSA C22.2 No 14<br>EN/IEC 60947-1<br>EN/IEC 60947-5-5<br>JIS C 4520<br>EN/IEC 60947-5-1<br>UL 508  |
| Product certifications                     | CSA<br>UL listed   |
| Vibration resistance                       | 5 gn (f = 12...500 Hz) conforming to IEC 60068-2-6   |
| Shock resistance                           | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |
| Resistance to fast transients              | 2 kV conforming to IEC 61000-4-4   |
| Resistance to electromagnetic fields       | 10 V/m conforming to IEC 61000-4-3   |
| Resistance to electrostatic discharge      | 6 kV on contact (on metal parts) conforming to IEC 61000-4-2<br>8 kV in free air (in insulating parts) conforming to IEC 61000-4-2   |
| Electromagnetic emission                   | Class B conforming to IEC 55011  |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Dimensions



- e : clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.
- b : 30 mm / 1.18 in.
- c : 46.5 mm / 1.83 in.

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board   | Connection by Faston Connectors  |
|---|--|
|    |  |
| <p>(1) Diameter on finished panel or support<br/>                 (2) 40 mm min. / 1.57 in. min.<br/>                 (3) 30 mm min. / 1.18 in. min.<br/>                 (4) <math>\varnothing 22.5 \text{ mm} / 0.89 \text{ in. recommended } (\varnothing 22.3 \text{ mm }_0^{+0.4} / 0.88 \text{ in. }_0^{+0.016})</math><br/>                 (5) 45 mm min. / 1.78 in. min.<br/>                 (6) 32 mm min. / 1.26 in. min.</p> |  |