

Product availability : Stock - Normally stocked in distribution facility

Price\* : 81.00 USD



### Main

Range	TeSys
Device short name	GVAU
Product or component type	Undervoltage trip

### Complementary

Product compatibility	GV2L GV2LE GV2ME GV2P GV3L GV3P
Control circuit voltage	24 V AC 50 Hz
Control circuit voltage limits	0.85...1.1 Un
[Ui] rated insulation voltage	600 V AC CSA C22.2 No 14 600 V AC UL 508 690 V AC IEC 60947-1
Threshold tripping voltage	0.7...0.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	8 W DC
Hold-in power consumption in VA	3.5 VA AC
Hold-in power consumption in W	1.1 W DC
Operating time	10...15 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 0...0 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible without Screw clamp terminals 1 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) solid Screw clamp terminals 2 0...0 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible without Screw clamp terminals 2 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) solid Screw clamp terminals 1 0...0 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> ) flexible with Screw clamp terminals 2 0...0 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> ) flexible with

Tightening torque	<= 12.39 lbf.in (1.4 N.m) screw clamp terminals
Mechanical durability	10000 cycles with GV3P and GV3L 30000 cycles with GV2ME and GV2P
Quantity per set	Set of 10
Product weight	0.23 lb(US) (0.105 kg)

### Ordering and shipping details

Category	22367 - MANUAL STR PROTECTOR - GV2
Discount Schedule	I11
Nbr. of units in pkg.	1
Package weight(Lbs)	0.25
Returnability	N
Country of origin	CZ

### Contractual warranty

Warranty period	18 months
-----------------	-----------