


HPP V4 RJ45 Cat5 plug 4p IDC



Part number	09 45 145 1100
Specification	HPP V4 RJ45 Cat5 plug 4p IDC
HARTING eCatalogue	https://b2b.harting.com/09451451100
Identification	
Category	Connector
Series	HARTING PushPull
Identification	RJ45
Element	Connector set

Version

Termination method	IDC termination
Locking type	PushPull
Shielding	Fully shielded, 360° shielding contact
Number of contacts	4
Pack contents	incl. housing with RJ45 connector, shielding and cable gland

Technical characteristics

Conductor cross-section	AWG 24/7 AWG 22/7 Stranded AWG 23/1 AWG 22/1 Solid
Limiting temperature	-40 +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67
Cable diameter	4.9 8.6 mm
Transmission characteristics	Cat. 5 Class D up to 100 MHz

Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No

Page 1 / 2 | Creation date 2018-10-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 45 145 1100 HPP V4 RJ45 Cat5 plug 4p IDC



Material properties	
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Specifications and approvals	
Specifications	IEC 61076-3-106 Variant 4
Commercial data	
Packaging size	1
Net weight	53.3 g
Country of origin	Romania
European customs tariff number	85366990