

外形图	型号 Model	颜色 Color	灯电压 Light voltage	外形尺寸 Overall dimension										
 A型信号灯 Indicator Light A type	AD56-16A	● 红-R  ● 绿-G  ● 黄-Y  ● 蓝-B  ○ 白-W	20-DC.AC 6V-36V (通用型)  21-DC.AC 6V  22-DC.AC 12V  23-DC.AC 24V  24-DC.AC 36V  25-DC.AC 48V  26-DC.AC 110V  27-DC.AC 127V  28-DC 220V  31-AC 220V  32-AC 380V											
	AD56-16AS													
 B型信号灯 Indicator Light B type	AD56-16B			● 红-R  ● 绿-G  ● 黄-Y  ● 蓝-B  ○ 白-W	20-DC.AC 6V-36V (通用型)  21-DC.AC 6V  22-DC.AC 12V  23-DC.AC 24V  24-DC.AC 36V  25-DC.AC 48V  26-DC.AC 110V  27-DC.AC 127V  28-DC 220V  31-AC 220V  32-AC 380V									
	AD56-16BS													
 C型信号灯 Indicator Light C type	AD56-16C					● 红-R  ● 绿-G  ● 黄-Y  ● 蓝-B  ○ 白-W	20-DC.AC 6V-36V (通用型)  21-DC.AC 6V  22-DC.AC 12V  23-DC.AC 24V  24-DC.AC 36V  25-DC.AC 48V  26-DC.AC 110V  27-DC.AC 127V  28-DC 220V  31-AC 220V  32-AC 380V							
	AD56-16CS													
 D型信号灯 Indicator Light D type	AD56-16D							● 红-R  ● 绿-G  ● 黄-Y  ● 蓝-B  ○ 白-W	20-DC.AC 6V-36V (通用型)  21-DC.AC 6V  22-DC.AC 12V  23-DC.AC 24V  24-DC.AC 36V  25-DC.AC 48V  26-DC.AC 110V  27-DC.AC 127V  28-DC 220V  31-AC 220V  32-AC 380V					
	AD56-16DS													
 E型信号灯 Indicator Light E type	AD56-16E									● 红-R  ● 绿-G  ● 黄-Y  ● 蓝-B  ○ 白-W	20-DC.AC 6V-36V (通用型)  21-DC.AC 6V  22-DC.AC 12V  23-DC.AC 24V  24-DC.AC 36V  25-DC.AC 48V  26-DC.AC 110V  27-DC.AC 127V  28-DC 220V  31-AC 220V  32-AC 380V			
	AD56-16ES													
 F型信号灯 Indicator Light F type	AD56-16F											● 红-R  ● 绿-G  ● 黄-Y  ● 蓝-B  ○ 白-W	20-DC.AC 6V-36V (通用型)  21-DC.AC 6V  22-DC.AC 12V  23-DC.AC 24V  24-DC.AC 36V  25-DC.AC 48V  26-DC.AC 110V  27-DC.AC 127V  28-DC 220V  31-AC 220V  32-AC 380V	
	AD56-16FS													

说明 Remarks

1. A、C、E为插脚接线方式；B、D、F为螺丝接线方式；S为超短型，无特殊要求将根据电压提供相应的产品
  2. 所以产品均采用纯色高亮度LED光源。
  3. 如需抗干扰（40V），抗浪涌请在定货时特别注明。
  4. φ16信号灯外壳均采用进口阻燃增强尼龙制作
  5. 透明外罩采用进口聚碳酸酯制作，外型美观，色泽鲜艳，抗高强度冲击。
1. The connection of A,C,E type is solder-terminal, the connection of B,D,F type is screw terminal; "S" is ultra-short type, According the voltage, To offer the counter products if no specification.
  2. All products use pure high illuminant LED light source
  3. Please clearly notice the specification, anti-interference (40V) and anti-surge.
  4. The material for body of 16mm indicator lamp is fire-retardant reinforced nylon.
  5. The material of Lamp cover is polycarbonate plastics, attractive shape, Bright in color, excellent in cushion effect.