DM87 True RMS

DMM with VSD MEASUREMENT



REF: 01VC87X0000 CE (EMC), UL, CE (LVD)

- 6,000 counts LCD display with bar graph
- True RMS AC measurement (up to 10kHz)
- VSD measurement: measures voltage and frequency of variable-speed drive (frequency converter) accurately
- Relative and Max /Min value measurement
- Auto-power off (approx. 30 min)
- Data hold and LCD backlit
- Full function protection and anti-magnetic, anti-jamming design
- Integrated holster, shock-proof
- Safety as per IEC1010-1 Cat.II 1000V

Technical specifications

DCV: $600 \text{m}/6/60/600/1000 \text{V}, \pm 0.5\%$

ACV: 6/60/600/750V, $\pm 0.8\%$ ($50\sim 20$ kHz)

VSD-V: 6/60/600/750V, ±2.0% (30~200Hz)

DCA: $600\,\mu/6m/60m/600m/6/20A,\,\pm1.0\%$

ACA: $600 \,\mu/6m/60m/600m/6/20A$, $\pm 1.2\%$

OHM: $600/6k/60k/600k/6M/30M\Omega$, $\pm 0.8\%$

CAP: $40n/400n/4 \mu/40 \mu/400 \mu/2000 \mu F$, $\pm 2.5\%$

FREQ: $5Hz\sim30MHz$, $\pm0.5\%$

TEMP: -40° C ~ 1000° C, 0° F ~ 1832° F, $\pm 0.8^{\circ}$

Duty cycle: 1% ~ 99%

Audible continuity: $<30 \Omega \pm 10 \Omega$

Transistor h_{FE} & diode test

Battery: 9Vx1, 6F22

Dimensions & weight: 185x93x35mm, ~290g

Accessories: holster, temp probe