

UT585

DIGITAL RCD /ELCB TESTER

- Auto-RAMP function for auto testing of trip time and trip current
- Large LCD display with backlit and function icon, displays trip time and current simultaneously
- Displays wiring status for connection checking
- 0 and 180 degree phase angle switch
- Auto display holding for easy reading
- Over-heat protection and test is prohibited automatically when inside temperature is high
- **Auto remote test, data logging**
- Maximum test current 2.5A
- Over-range display
- Low battery indication
- Double insulated, fuse protection
- Auto power off
- High stability, easy operation, ideal for inexperienced users

REF: 04U585X0000

✓ CE (EMC), □ UL, ✓ CE (LVD)



Technical Specifications

Rated trip current:

10m /20m/30m/100m/300m/500mA, $\pm 2\%$

Range select: x1/2, x1, x2, x5, Auto RAMP

Trip time: 2000ms /200ms(x5), $\pm 1\%$

Trip time resolution: 1ms

ACV measurement: 60~440V (45~65Hz), $\pm 3\%$

DCV measurement: 60~440V, $\pm 3\%$

Operating voltage: 230V $\pm 10\%$ /50Hz

Phase switch: 0° or 180°

Batteries: 1.5V x8, AA size

Dimensions: 210x175x90mm, 1000g approx.

Accessories: tool case

Sinometer