



UT60H True RMS

MODERN DMM, HIGH ACCURACY

- 40,000 counts LCD display with analog bar graph and LCD backlit
- Data hold, sleep mode
- True RMS, Max /Min /relative measurement
- **Non-contact voltage detection** (EF function)
- **4~20mA loop** feature (Lo-%-Hi display)
- Low impedance ($200k\ \Omega$) selection
- Enhanced protection, 10A fused
- Safety as per IEC1010-1, **Cat. III 1000V**

Technical specifications

DCV: 4/40/400/1000V, $\pm 0.1\%$

ACV: 4/40/400/750V, $\pm 1.0\%$

DCA: 400 μ /4m/40m/400m/10A, $\pm 0.5\%$

ACA: 400 μ /4m/40m/400m/10A, $\pm 1.2\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 0.5\%$

CAP: 40n/400n/4 μ /40 μ /400 μ /4m/40mF, $\pm 1.5\%$

TEMP: $-40^{\circ}\text{C} \sim 400^{\circ}\text{C}$, $\pm 1.0\%$

FREQ: 4k/40k/400k/4M/40M/100MHz, $\pm 0.01\%$

EF function: AC 50~400V

Audible continuity & diode test

Battery: 9Vx1, 6F22

Dimensions: 177x85x40mm, approx. 312g

Accessories: holster, temp probe

REF: 01UT60H0000

☒ CE (EMC), ☐ UL, ☐ CE (LVD)