

Ordering chart for compact flow transmitter Type SE36

Specification	Voltage supply	Output	Electrical connection	UL certification	Article no. without display/ configuration module	Article no. with display/ configuration module
2 outputs	14 ... 36 V DC	1 x transistor NPN + 1 x 4 ... 20 mA (2 wires)	5 pin M12 male fixed connector	No	560880	561880
				Recognized	560883	561883
3 outputs	14 ... 36 V DC	2 x transistors NPN/PNP + 1 x 4 ... 20 mA (2 wires)	5 pin M12 male fixed connector	No	560881	561881
				Recognized	560884	561884
4 outputs	12 ... 36 V DC	2 x transistors NPN/PNP + 2 x 4 ... 20 mA (2 wires)	5 pin M12 male and 5 pin M12 female fixed con- nectors	No	560882	561882
				Recognized	560885	561885

Note: Order separately (see accessories)

- M12 cable plugs (only female for one 4 ... 20 mA output, 1 male + 1 female for two 4 ... 20 mA outputs flowmeter)

Ordering chart - accessories (has to be ordered separately)

Specification	Article no.
Removable display/configuration module (with instruction sheet)	559168
Blind cover with seal (1 screw cover with EPDM seal + 1 quarter turn closing cover with silicone seal)	560948
Transparent cover with seal (1 screw cover with EPDM seal + 1 quarter turn closing cover with silicone seal)	561843
5 pin M12 female straight cable plug with plastic threaded locking ring, to be wired	917116
5 pin M12 male straight cable plug with plastic threaded locking ring, to be wired	560946
5 pin M12 female straight cable plug moulded on cable (2 m, shielded)	438680
5 pin M12 male straight cable plug moulded on cable (2 m, shielded)	559177