

## Complete units: Pushbuttons $\varnothing$ 22

IP 66 - IP 69K  
 Complete units consisting of:  
 - head  
 - clip and screw electrical blocks assembled  
 Plastic chrome bezel - Black bezel on request (form p. 83)  
 Conform to IEC 60947-5-1



Characteristics (p. 98)


### ► SPRING RETURN - ILLUMINATED

#### FLUSH


Cat. No.



L21AH20L



LED blocks



**24V**

- Red
- Green
- Yellow
- White
- Blue

- NO+NC
- NO+NC
- NO+NC
- NO+NC
- NO+NC

- L21AH10L**
- L21AH20L**
- L21AH40L**
- L21AH50L**
- L21AH60L**

**130 V**

- Red
- Green

- NO+NC
- NO+NC

- L21AH10M**
- L21AH20M**

**230 V**

- Red
- Green

- NO+NC
- NO+NC


- L21AH10H**
- L21AH20H**

#### TWIN TOUCH - FLUSH-PROJECTING


Degree of protection: IP 66



L61QK21H



LED blocks  
 Central part illuminated



**24 V**

- Green
- Red

- NO
- NC

- L61QK21L**

**130 V**

- Green
- Red

- NO
- NC

- L61QK21M**

**230 V**

- Green
- Red

- NO
- NC

- L61QK21H**