# Product data sheet Characteristics

## NSYSBM15158

Metal industrial box plain door H150xW150xD80 IP66 IK10 RAL 7035





#### Main

Range	Spacial	
Product name	Spacial SBM	
Device application	Multi-purpose	
Category	Industrial box	
Device short name	SBM	
Enclosure type	Flat face box	
Enclosure nominal height	150 mm	
Enclosure nominal width	150 mm	
Enclosure nominal depth	80 mm	
Enclosure mounting	Wall mounted	: E
Device composition	4 cover screw	
	1 cover	Š
	1 body	ğ
Body type	Single piece body folded and welded	
Type of front cover	Plain door	+
Cover fixing	Half turn metal screw	<u>.</u>
Lock type	Captive screw PZ2 outside sealed area	
Removable parts	Cover by captive screws	
		<del>-</del>

#### Complementary

Material	Sheet steel	ā
Surface finish	Polyester powder	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	i i
Product certifications	UL GL DNV LR BV	claimer. This docum

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for storage	-3560 °C
Operating temperature	-3580 °C
Net weight	1.114 kg

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

#### Contractual warranty

144	10
Warranty	18 months
vvarianty	TO MONATO