

# PV-male and female cable coupler MC4



## PV- male and female cable coupler MC4

With Snap-in lock

### Material

Polyamide  
Contact:Cu, tinned, rotated

### Technical data

Protection classification: IP 67  
Safety class: II  
Temperature range: -40°C up to +90°C  
Rated voltage: 1000 V (IEC)  
Rated current: 22A (2,5 mm<sup>2</sup>), 30A (4mm<sup>2</sup>, 6mm<sup>2</sup>)  
Contact resistance of plug connectors: 0.35 mOhm

### MC4 male cable coupler

Part no.	Designation	Cross section mm <sup>2</sup>	Cable Ø mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
905206	PV-male cable coupler MC4	2,5	3 - 6	50	o. r.	o. r.	o. r.
905208	PV-male cable coupler MC4	2,5	5,5 - 9	50	o. r.	o. r.	o. r.
905210	PV-male cable coupler MC4	4 - 6	3 - 6	50	o. r.	o. r.	o. r.
904963	PV-male cable coupler MC4	4 - 6	5,5 - 9	50	o. r.	o. r.	o. r.
905863	PV-male cable coupler MC4	10	5,5 - 9	50	o. r.	o. r.	o. r.

### MC4 female cable coupler

Part no.	Designation	Cross section mm <sup>2</sup>	Cable Ø mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
905207	PV-female cable coupler MC4	2,5	3 - 6	50	o. r.	o. r.	o. r.
905209	PV-female cable coupler MC4	2,5	5,5 - 9	50	o. r.	o. r.	o. r.
905211	PV-female cable coupler MC4	4 - 6	3 - 6	50	o. r.	o. r.	o. r.
904964	PV-female cable coupler MC4	4 - 6	5,5 - 9	50	o. r.	o. r.	o. r.
905864	PV-female cable coupler MC4	10	5,5 - 9	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request