

wobble stick - black - unmarked - base of enclosure - sale per 1

ZA2BB2

Product availability: Stock - Normally stocked in distribution facility

Price*: 153.00 USD

Main

Range of Product	Harmony XAC
Product or Component Type	Wobble stick
Component name	ZA2
Product Compatibility	XACA

Complementary

Marking	Unmarked
Cap/Operator or lens colour	Black
Mounting Location	Base of enclosure
Sale per indivisible quantity	1
Net Weight	0.13 lb(US) (0.06 kg)

Environment

Standards	UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60204-32
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Vibration resistance	15 gn 10500 Hz)IEC 60068-2-6
Overvoltage category	Class II IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 EN 50102

Ordering and shipping details

Category	22460-PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2
GTIN	3389110591224
Returnability	No

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	FR
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.0 cm)
Package 1 Width	1.18 in (3.0 cm)
Package 1 Length	4.13 in (10.5 cm)
Package 1 Weight	2.12 oz (60.0 g)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Contractual warranty	
Warranty	18 months

Recommended replacement(s)