Product data sheet

Specifications





Linergy FT, Comb busbar, 63A, 2 tap-offs, 54mm pitch

GV2G254

Product availability: Stock - Normally stocked in distribution facility

Main

RangeLinergyProduct NameFTDevice Short NameGV2GProduct Or Component TypeComb busbarAccessory / Separate Part CategoryConnection accessoryPoles Description3PRange CompatibilityTeSys GV2 TeSys K TeSys U TeSys DecaNumber Of Tap-Offs2Ith] Conventional Free Air Thermal Current63 AConnection Pitch2.13 in (54 mm)		
Device Short Name GV2G Product Or Component Type Comb busbar Accessory / Separate Part Connection accessory Category Separate Part Poles Description 3P Range Compatibility TeSys GV2 TeSys K TeSys U TeSys Deca Number Of Tap-Offs 2 Ith] Conventional Free Air Thermal Current 63 A	Range	Linergy
Product Or Component Type Comb busbar Accessory / Separate Part Connection accessory Category Connection accessory Poles Description 3P Range Compatibility TeSys GV2 TeSys K TeSys U TeSys Deca Number Of Tap-Offs 2 [Ith] Conventional Free Air Thermal Current 63 A	Product Name	FT
Accessory / Separate Part Connection accessory Poles Description 3P Range Compatibility TeSys GV2 TeSys K TeSys U TeSys Deca Number Of Tap-Offs 2 [Ith] Conventional Free Air Thermal Current 63 A	Device Short Name	GV2G
Category 3P Poles Description 3P Range Compatibility TeSys GV2 TeSys K TeSys U TeSys Deca Number Of Tap-Offs 2 [Ith] Conventional Free Air Thermal Current 63 A	Product Or Component Type	Comb busbar
Range Compatibility TeSys GV2 TeSys K TeSys U TeSys Deca Number Of Tap-Offs 2 [Ith] Conventional Free Air Thermal Current 63 A		Connection accessory
TeSys K TeSys U TeSys Deca Number Of Tap-Offs 2 [Ith] Conventional Free Air 63 A Thermal Current	Poles Description	3P
[Ith] Conventional Free Air 63 A Thermal Current	Range Compatibility	TeSys K TeSys U
Thermal Current	Number Of Tap-Offs	2
Connection Pitch 2.13 in (54 mm)		63 A
	Connection Pitch	2.13 in (54 mm)

Complementary

Mounting Location	On terminal
[Ui] Rated Insulation Voltage	690 V
Length	3.86 in (98 mm)
Net Weight	0.08 lb(US) (0.038 kg)

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0111
Gtin	3389110555936
Returnability	Yes
Country Of Origin	RO

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.39 in (1 cm)
Package 1 Width	3.15 in (8 cm)
Package 1 Length	5.51 in (14 cm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Package 1 Weight	1.41 oz (40 g)
Unit Type Of Package 2	S01
Number Of Units In Package 2	80
Package 2 Height	5.91 in (15 cm)
Package 2 Width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	7.24 lb(US) (3.285 kg)
Unit Type Of Package 3	P06
Number Of Units In Package 3	2560
Package 3 Height	30.31 in (77 cm)
Package 3 Width	31.50 in (80 cm)
Package 3 Length	23.62 in (60 cm)
Package 3 Weight	260.37 lb(US) (118.1 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


Product data sheet

Dimensions Drawings

Sets of Busbars $\mathsf{GV2G}_{\bullet\bullet\bullet}$ with Terminal Block $\mathsf{GV1G09}$



Sets of Busbars GV2G245, GV2G254, GV2GR272



	I
GV2G245 (2 x 45 mm)	89
GV2G254 (2 x 54 mm)	98
GV2G272 (2 x 72 mm)	116