

# Product data sheet

Specifications



## TeSys Deca Manual Starter and Protector, auxiliary contact block, 1 NO and 1 NC, top mount, screw clamp

GVAE11

### Main

Range	TeSys TeSys Deca
Device Short Name	GVAE
Product Or Component Type	Auxiliary contact block
Product Compatibility	GV2P GV2RT GV2ME GV3L GV2LE GV3P GV2L
Mounting Location	Front side
Pole Contact Composition	1 NO + 1 NC
Quantity Per Set	Set of 10

### Complementary

[Ui] Rated Insulation Voltage	300 V UL 508 300 V CSA C22.2 No 14 250 V IEC 60947-1
[Ue] Rated Operational Voltage	24...240 V AC 24...60 V DC
[Ith] Conventional Free Air Thermal Current	2.5 A
Mechanical Durability	100000 cycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Protection Type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Rated Operational Power In Va	120 VA 110...120 V AC-15 100000 cycles 120 VA 230...240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles
Rated Operational Power In W	15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles
Tightening Torque	12.39 lbf.in (1.4 N.m) screw clamp terminals
Height	0.43 in (11 mm)
Width	1.77 in (45 mm)

Depth	1.14 in (29 mm)
Net Weight	0.04 lb(US) (0.02 kg)

## Environment

Environmental Characteristic	Normal environment
Product Certifications	UKCA

## Ordering and shipping details

Category	US10I1122367
Discount Schedule	0I11
Gtin	3389110343434
Returnability	Yes
Country Of Origin	CZ

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.47 in (1.200 cm)
Package 1 Width	2.36 in (6.000 cm)
Package 1 Length	2.76 in (7.000 cm)
Package 1 Weight	0.60 oz (17.000 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	2.44 in (6.200 cm)
Package 2 Width	4.72 in (12.000 cm)
Package 2 Length	2.91 in (7.400 cm)
Package 2 Weight	6.14 oz (174.000 g)
Unit Type Of Package 3	S02
Number Of Units In Package 3	220
Package 3 Height	5.91 in (15.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	9.09 lb(US) (4.123 kg)

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

**Circularity Profile**

[End of Life Information](#)

**California Proposition 65**

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

GVAE11

