Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# **Product datasheet**

Specifications





## Auxiliary contact block,TeSys Control,1 NO + 1 NO,for V02-V6

VZ20

#### Main

Range	TeSys	
Device Short Name	VZ	
Product Or Component Type	Auxiliary contact block	
Performance Level	High performance	
Contacts Type And Composition	1 NO + 1 NO	
Product Compatibility	V3	
	V01	
	V2	
	V0	
	V6	
	V4	
	V1	
	V5	
	V02	
Network Type	DC	
	AC	
Network Frequency	50/60 Hz	
Mounting Location	Left	
	Right	

### Complementary

[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	12 A
[Ithe] Conventional Enclosed Thermal Current	10 A
Mechanical Durability	100000 cycles
Electrical Durability	30000 cycles DC-11 100000 cycles AC-15
Connections - Terminals	Screw clamp terminals 2 cable(s) 0.751.5 mm² - flexible - with cable end Screw clamp terminals 2 cable(s) 12.5 mm² - solid
Tightening Torque	0.7 N.m - on screw clamp terminals
Height	65 mm
Width	20 mm
Depth	48.5 mm
Net Weight	0.05 kg

#### **Environment**

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Standards	IEC 60947-5
Product Certifications	GL UL CSA UKCA
Protective Treatment	TC
Ip Degree Of Protection	IP20 conforming to IEC 60529
Ambient Air Temperature For Operation	-2050 °C
Fire Resistance	960 °C conforming to IEC 60695-2-1

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	5.500 cm
Package 1 Length	9.000 cm
Package 1 Weight	54.400 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	69
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.001 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	
<b>⊘</b>	Halogen Free Product	

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations