

single isolating block XACS - for power circuit - horizontal fixing centres-40mm

XACS399

Main

| Range Of Product | Harmony XAC | |
|-------------------------------|----------------------------|--|
| Product Or Component Type | Isolating block | |
| Component Name | XACS | |
| Electrical Circuit Type | Power circuit | |
| Contact Block Application | Emergency stop push-button | |
| Contact Block Type | Single | |
| Product Compatibility | XACB | |
| Contacts Type And Composition | 3 NC | |
| Mounting Of Block | Front mounting | |
| Contact Operation | Snap action | |

Complementary

| Connections - Terminals | Screw clamp terminals, $1 \times 2.5 \text{ mm}^2$ with or without cable end Screw clamp terminals, $2 \times 1.5 \text{ mm}^2$ with or without cable end | |
|---|---|--|
| Horizontal Fixing Centres | 40 mm | |
| Mechanical Durability | 1000000 cycles | |
| Contact Code Designation | A300 AC-15, Ue = 240 V, Ie = 3 A conforming to IEC 60947-5-1 appendix A Q300 DC-13, Ue = 250 V, Ie = 0.27 A conforming to IEC 60947-5-1 appendix A | |
| [Ui] Rated Insulation Voltage | 400 V (pollution degree 3) conforming to IEC 60947-1 | |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to IEC 60947-1 | |
| Rated Operational Power In W | 3000 W AC-23B at 400 V | |
| Net Weight | 0.1 kg | |

Environment

| Standards | IEC 60947-3 IEC 60947-3 CSA C22.2 No 14 |
|---------------------------------------|---|
| Ambient Air Temperature For Operation | -2570 °C |
| Ambient Air Temperature For Storage | -4070 °C |
| Vibration Resistance | 15 gn (f= 10500 Hz) conforming to IEC 60068-2-6 |
| Shock Resistance | 100 gn conforming to IEC 60068-2-27 |
| Electrical Shock Protection Class | Class II conforming to IEC 61140 |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.4 cm |
| Package 1 Width | 8.2 cm |
| Package 1 Length | 9.6 cm |
| Package 1 Weight | 88.0 g |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 50 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 4.423 kg |

Contractual warranty

Warranty 12 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| ② | Reach Free Of Svhc | |
|----------|----------------------------|---|
| | Toxic Heavy Metal Free | |
| | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |
| | | |
| Rea | ch Regulation | REACh Declaration |
| Eu F | Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Chir | na Rohs Regulation | China RoHS declaration |
| Wee | е | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |