



Solenoid: 24V DC, 1/4 in to 3/4 in, 3.0 to 12.0 oz, 1 1/2 in Dp, 1 5/8 in Lg, 1 7/16 in Wd

Item 1KEK7

Mfr. Model B22-253-M-36

Compare

Product Details Catalog Page N/A

Brand **DORMEYER**

Solenoid Type **Box Frame**

Stroke Range **1/4 in to 3/4 in**

Pull Force Range **3.0 to 12.0 oz**

Width **1-7/16 in**

Depth **1-1/2 in**

Length **1-5/8 in**

Body Length **1-5/16 in**

Coil Volts **24V DC**

Seated Amps **0.41 A**

Seated Watts **9.9 W**

Coil Resistance **58.2 ohm**

Coil Insulation **Class A**

Terminals **3/16 in Quick Connect**

Amps @ Max. Stroke **0.41 A**

Duty Cycle **Continuous**

Material of Construction **Steel**

From Mounting Holes to Plunger Hole **27/32 in**

Gravity Value **1.4 oz**

Standards **RoHs**

Pull @ 1/2 In. Stroke **1 oz**

Pull @ 3/8 In. Stroke **5 oz**

Pull @ 1/4 In. Stroke **15 oz**

Pull @ 1/8 In. Stroke **24 oz**

UNSPSC **31251510**

Country of Origin **USA (subject to change)**

Product Description

Solenoids are designed to provide the mechanical movement of a plunger.