

Product datasheet

Specifications



mechanical interlocking kit,
ComPact NS630b to NS1600, for 2
devices with extended rotary
handles

33890

Main

Product Or Component Type	Mechanical interlock
Accessory / Separate Part Category	Interlocking accessory
Range Compatibility	ComPact ComPact NS630b...1600

Complementary

Source-Changeover Interlock	Interlocking 2 sources
Interlocked Device	Compact NS630b...1600
Control Type	Extended rotary handle
Accessory / Separate Part Category	Spare part for Compact NS630b...1600

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.7 cm
Package 1 Width	18.0 cm
Package 1 Length	43.0 cm
Package 1 Weight	807.0 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	18
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	15.526 kg

Contractual warranty

Warranty	18 months
----------	-----------

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability




Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

	Mercury Free	
<hr/>		
	Rohs Exemption Information	Yes
<hr/>		
	Pvc Free	
<hr/>		
Reach Regulation		REACH Declaration
<hr/>		
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope)
<hr/>		
China Rohs Regulation		China RoHS declaration
<hr/>		