



**Solenoid: 120V AC, 1/8 in to 1 in, 88.0 to 168.0 oz, 2 1/16 in Dp, 2 1/2 in Lg, 2 1/16 in Wd**

Item **4X241** Mfr. Model **2536-M-1**

Compare

## Product Details

Catalog Page **N/A**

Brand **DORMEYER**

Solenoid Type **Laminated**

Stroke Range **1/8 in to 1 in**

Pull Force Range **88.0 to 168.0 oz**

Width **2-1/16 in**

Depth **2-1/16 in**

Length **2-1/2 in**

Coil Volts **120V AC**

Seated Amps **0.48 A**

Seated Watts **19 W**

Coil Resistance **14.9 ohm**

Terminals **Solder Lug Coil**

Amps @ Max. Stroke **6.5 A**

Duty Cycle **Continuous**

Mounting Holes **2 x 1-5/8 in**

Gravity Value **5.92 oz**

Pull @ 3/4 In. Stroke **3 oz**

Pull @ 1 In. Stroke **1 oz**

Pull @ 5/8 In. Stroke **5 oz**

Pull @ 1/2 In. Stroke **13 oz**

Pull @ 3/8 In. Stroke **20 oz**

---

Pull @ 1/4 In. Stroke **35 oz**

---

Pull @ 1/8 In. Stroke **65 oz**

---

UNSPSC **31251510**

---

Country of Origin **USA (subject to change)**

---

Product Description

Solenoids are designed to provide the mechanical movement of a plunger.