

**Solenoid: 24V DC, 1/16 in to
5/8 in, 3.8 to 58.0 oz, 2 7/16
in Lg, Tubular, Intermittent**Item **5AA34** Mfr. Model **195206-231** Compare**Product Details** Catalog Page **N/A**Brand **LEDEX**Solenoid Type **Tubular**Stroke Range **1/16 in to 5/8 in**Pull Force Range **3.8 to 58.0 oz**Dia. **1 in**Length **2-7/16 in**Body Length **2-7/16 in**Coil Volts **24V DC**Seated Amps **0.36 A**Seated Watts **10 W**Coil Resistance **77.4 ohm**Coil Insulation **Class A**Terminals **10 in Leads**Amps @ Max. Stroke **0.36 A**Duty Cycle **Intermittent**Gravity Value **1.46 oz**Pull @ 3/4 In. Stroke **7 oz**Pull @ 1 In. Stroke **5 oz**

Pull @ 5/8 In. Stroke **10 oz**

Pull @ 1/2 In. Stroke **18 oz**

Pull @ 3/8 In. Stroke **22 oz**

Pull @ 1/4 In. Stroke **35 oz**

Pull @ 1/8 In. Stroke **73 oz**

UNSPSC **31251510**

Country of Origin **USA (subject to change)**

Product Description

Solenoids are designed to provide the mechanical movement of a plunger.