Product datasheet

Specifications

trip unit accessory - SDTAM 24/415V AC/DC - for NSX100..250 / NSX400..630

LV429424

Main

Range Of Produc	ComPact NSX100...250 ComPact NSX400...630
Range	ComPact
Device Short Name	SDTAM
Product Or Component Type	Thermal fault module
Device Application	Signalling
Range Compatibility	ComPact ComPact NSX circuit breaker
Accessory / Separate Part Category	Trip unit accessory
Trip Unit Name	MicroLogic 2.3 M MicroLogic 2.2 M MicroLogic 6.3 E-M MicroLogic 6.2 E-M

Complementary

Maximum Output Current	0.08 A
[Us] Rated Supply Voltage	24...415 V AC 50/60 Hz 24...415 V DC

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	5.0 cm
Package 1 Length	10.5 cm
Package 1 Weight	58.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	46
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.123 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Life Is On | Schneider Electric