Product datasheet

Specifications

Green Premium™



ClimaSys CC - simple thermostat 250V - range of temperature 0... 60°C - NO - °C

NSYCCOTHO

Main

| Range | ClimaSys |
|---------------------------|-------------------|
| Product Name | ClimaSys CC |
| Product Or Component Type | Simple thermostat |
| Temperature Setting Range | 060 °C |
| Information Displayed | Temperature in °C |

Complementary

| Complementary | |
|--|--|
| Input Voltage | 250 V |
| Sensor Type | Bimetal |
| Contacts Type And Composition | NO |
| Contact Resistance | 10 mOhm |
| Service Life In Cycles | 100000 cycles |
| Maximum Switching Capacity | 2 A 120250 V AC inductive pf: 0.6 10 A 250 V AC resistive 15 A 120 V AC resistive 30 W DC |
| Electrical Connection | 4 terminals, clamping capacity: 2.5 mm ² |
| Mounting Mode | Clipped |
| Height | 68 mm external: |
| Width | 33 mm external: |
| Depth | 44 mm external: |
| Net Weight | 40 g |
| Mounting Location | 35 mm DIN rail On mounting plate Cross rails Spacial upright |
| Ambient Air Temperature For Operation | -2080 °C |
| Ip Degree Of Protection | IP20 |
| Hysteresis | 7 K +/- 0.4K |
| Number Of Outputs | 1 ventilation function |
| Material | PC |
| Colour | Light grey |
| Flame Retardance | Self-extinguishing conforming to UL94 (material V0) |
| Product Certifications | UL |

Packing Units

| U | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.5 cm |
| Package 1 Width | 6.0 cm |
| Package 1 Length | 8.0 cm |
| Package 1 Weight | 64.0 g |
| Unit Type Of Package 2 | CAR |
| Number Of Units In Package 2 | 100 |
| Package 2 Height | 24.0 cm |
| Package 2 Width | 33.0 cm |
| Package 2 Length | 41.0 cm |
| Package 2 Weight | 7.588 kg |
| Unit Type Of Package 3 | P12 |
| Number Of Units In Package 3 | 3600 |
| Package 3 Height | 166.0 cm |
| Package 3 Width | 80.0 cm |
| Package 3 Length | 120.0 cm |
| Package 3 Weight | 280.0 kg |
| | |

Contractual warranty

Warranty

12 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |