



CM68C True RMS

100A AC/DC MINI CLAMP METER

- 2,000 counts LCD display with backlit
- **True RMS** AC measurement
- Non-contact AC voltage detection (NCV)
- Data hold, DCA zero adjustment
- Auto range, auto power off
- Safety as per IEC1010-1 Cat.III 600V

Technical specifications

DCV: 200m/2/20/200/600V, $\pm 0.5\%$

ACV: 2/20/200/600V, $\pm 1.0\%$ (40Hz~1kHz)

DCA: 2/20/100A, $\pm 2.5\%$

ACA: 2/20/100A, $\pm 2.5\%$ (40Hz~400Hz)

OHM: 200/2k/20k/200k/2M/20M Ω , $\pm 0.8\%$

CAP: 200n/2 μ /20 μ /200 μ /2mF, $\pm 3.5\%$

TEMP: -20 $^{\circ}$ C~1000 $^{\circ}$ C, -4 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 2.0\%$

Audible continuity (<50 Ω) & diode test

Clamp size: $\Phi 25$ mm

Battery: 1.5Vx2, AAA size

Dimensions: 165x56x31mm, 140g approx.

Accessories: carrying bag

REF: 03CM85C0000

CE (EMC), UL, CE (LVD)

Sinometer