



Basic Info.

Model NO.	JRQFS650BA	Operating Voltage	220-240V AC 50/60Hz
Heating Capacity 50Hz	530-570W	Heating Capacity 60Hz	630-670W
Inrush Current Max	13A	Pre-Fuse Time 230V AC,120VAC	8A
Airflow Free Flow	45m ³ /H	Setting Range Temp.	0~+60°C
Casing	UL94-Vo, Light Grey	Transport Package	Seaworthy Carton
Trade mark	LEIPOLE	Origin	Shanghai
HS Code	85168000	Production Capacity	100000PC/Year

Product Description

Model	Operating Voltage	Heating Capacity 50Hz	Heating Capacity 60Hz	Inrush Current Max.	Pre-fuse(time -delay) 230VAC/120VAC
JRQFS650BA	220-240VAC 50/60Hz	530-570W	630-670W	13A	8A

Heating element	PTC resistor-temperature limiting
Temperature safty cut-out	to protect against overheating in case of fan failure,automatic reset
Axial fan ,ball bearing	airflow see table service life 50,000h at 25°C(77°F)

Electrical connection	2 pole clamp 2.5mm ² ,clamping torque 0.8Nm max
Connection casing	plastic according to UL94V-0,black
Optical Indicator	Thermostat Control Lamp
Installation	clip for 35mm Din rail,EN 60715
Fitting position	Vertical airflow(air outlet up)
Operating/storage areas	-45°C to +70°C (-49°F ~ +158°F)
Operating/storage humidity	max.90% RH(non-condensing)
Protection class	IP20