

Product data sheet

Specifications



Climasys CC - electronic hydrotherm - 95 to 135V - temp -40 to 80 C - Hr 20 to 80%

NSYCCOHYT120VID

Overview

Lead time Usually Ships within 4 Weeks

Main

Range	ClimaSys
Product name	ClimaSys CC
Product or Component Type	Electronic hydrotherm
Temperature setting range	-40...176 °F (-40...80 °C)
Humidity setting range	20...80 %
Display Type	OLED screen
Information Displayed	Temperature in °F Relative humidity Temperature in °C

Complementary

Input voltage	90...140 V AC
Sensor Type	Optional NTC external sensor
Maximum switching capacity	4 A 120 V AC
Electrical connection	8 connectors 2.5 mm ²
Mounting Mode	By screws Clipped
Height	External: 3.3 in (85 mm)
Width	External: 2.2 in (56 mm)
Depth	External : 1.7 in (44 mm)
mounting location	35 mm DIN rail Cross rails On mounting plate Spacial upright
Ambient Air Temperature for Operation	-40...176 °F (-40...80 °C)
Hysteresis	2 K programmed value
Hysteresis	3 %
Number of outputs	2 ventilation/heating function
Material	PC
Color	Light gray

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Flame retardance	Self-extinguishing conforming to UL94 (material V0)
------------------	---

Product Certifications	UR
------------------------	----

Ordering and shipping details

Category	US10ES180036
----------	--------------

Discount Schedule	0ES1
-------------------	------

GTIN	3606480152580
------	---------------

Returnability	Yes
---------------	-----

Country of origin	US
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	2.300 in (5.842 cm)
------------------	---------------------

Package 1 Width	3.0000000000 in (7.62 cm)
-----------------	---------------------------

Package 1 Length	3.400 in (8.636 cm)
------------------	---------------------

Package 1 Weight	5.600 oz (158.759 g)
------------------	----------------------

Contractual warranty

Warranty	18 months
----------	-----------
